



ASR
Refrigeración

EQUIPO CENTRAL

B Air
TU CLIMA DE CONFIANZA

LINEA PAQUETE		BAP140361CM	BAP140481CM	BAP140601CM
Suministro Eléctrico		V,HZ,Ph	208/230-1-60HZ	208/230-1-60HZ
Enfriamiento	Capacidad	Btu/h	36000	48000
	Input	W	3008	4075
	SEER	W/W	14	14
Calefacción	Capacidad	Btu/h	34200	48600
	Input	W	2528	3732
	SEER	W/W	8	8
Entronque de extracción		pig	14.5x14.5	14.5x14.5
Entronque de succión		pig	14.5x18	14.5x24
MCA		A	21.4	26.9
MOP		A	30	40
Tipo de compresor			Scroll	Scroll
Corriente máxima		A	30.0	40.0
Corriente inicial		A	75.0	108.0
Unidad	Dimensión (Ancho*Profundo*Alto)	cm	132.1x63x95.8	148x84x106.8
	Peso del Empaque	kg	162	214
Nivel de Ruido Exterior		dB(A)	67.5	67.5
Tipo de Refrigerante		lbs-oz	R410a/4-14	R410a/6-13



Garantía
5 años en compresor
1 año en partes



(662)301-3041



info@asrefrigeracion.mx



asrefrigeracion

TONELADAS			7.5	10	15
MODELO			BAP110903CM	BAP111203CM	BAP111803CM
Cooling	Capacity (1)	Btu/h	89,000	120,000	180,000
		W	26,100	35,200	52,800
	Input (1)	W	7,800	10,700	16,200
	EER (1)	Btu/h.W	11.4	11.2	11.1
Air Flow	Indoor side	DFM	2,700	4,120	6,450
External static pressure		Pa	Default: 80; 0 - 250	Default: 90; 0 - 250	Default: 110; 0 - 300
Max. Power input		W	11,300	17,500	25,000
Max. Current		A	42.4	57.4	88.3
Compressor	Type/Quantity		Scroll/1	Scroll/1	Scroll/2
	Brand		Copeland	Copeland	Copeland
Indoor fan	Type/Drive type		Centrifugal/direct	Centrifugal/Belt	Centrifugal/Belt
Outdoor fan	Type/Drive type		Axial/ Direct	Axial/ Direct	Axial/ Direct
Wired controller			KJR-25B	KJR-12B/dP(T)-E	KJR-12B/dP(T)-E
Centralized controller (optional)			Yes	Yes	Yes
Sound pressure level		dB(A)	75.6	75.7	76.6
Ambient temperatura			10°C – 52°C	10°C – 52°C	10°C – 52°C
Dimension	Net (WxHxD)	Mm	1,475x840x1,130	1,483x1,231x1,138	1,965x1,230x1,130
	Packing (WxHxD)	Mm	1,495x870x1,150	1,500x1,255x1,155	1,995x1,160
Weight	Net/Gross	kg	235/240	325/335	470/485